

according to 29 CFR 1910.1200(g)

Cutting Fluid Silberschnitt V52

Revision date: 03/17/2022 Product code: BO5002904 Page 1 of 8

1. Identification

Product identifier

Cutting Fluid Silberschnitt V52

Further trade names

BO5002954, 5 I BO5002904, 30 I BO5002934, 200 I BO9973880*, Sample

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

cutting fluid

Details of the supplier of the safety data sheet

Manufacturer

Company name: BOHLE AG
Street: Dieselstr. 10
Place: 42781 Haan
Telephone: +49 2129 5568-0

Felephone: +49 2129 5568-0 Telefax: +49 2129 5568-282

e-mail: info@bohle.de

Contact person: Dr. Martin Schade Telephone: +49 2129 5568-300

e-mail: MSDS@bohle.de lnternet: www.bohle.com

Responsible Department: Chemie

Trader of the product

Company name: Bohle America, Inc.

Street: 10924 Granite Street, Suite 200
Place: USA-NC 28273 Charlotte

e-mail (Contact person): sales@bohle.com

Emergency phone number: Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

2. Hazard(s) identification

Classification of the chemical

29 CFR Part 1910.1200

Flammable liquids: Flam. Liq. 3 Aspiration hazard: Asp. Tox. 1 Skin corrosion/irritation: Skin Irrit. 2

Label elements

29 CFR Part 1910.1200

Signal word: Danger

Pictograms:







Hazard statements

Flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation



according to 29 CFR 1910.1200(g)

Cutting Fluid Silberschnitt V52

Revision date: 03/17/2022 Product code: BO5002904 Page 2 of 8

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Store in a well-ventilated place. Keep cool.

Store locked up.

3. Composition/information on ingredients

Mixtures

Chemical characterization

Hydrocarbons

Hazardous components

CAS No	Components	Quantity
68551-17-7	Hydrocarbons, C10-C13, isoalkanes, cyclics, <2% aromatics	<50 %
93924-07-3	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	<50 %
93924-07-3	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics	<25 %
5131-66-8	3-butoxypropan-2-ol, propylene glycol monobutyl ether	<10 %

4. First-aid measures

Description of first aid measures

General information

First aider: Pay attention to self-protection!

Move out of dangerous area.

Take off contaminated clothing and shoes immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

If symptoms persist, call a physician.

After contact with skin

Wash off with soap and plenty of water.

If symptoms persist, call a physician.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses, if present and easy to

do. Continue rinsing.

Consult a physician.

After ingestion

Rinse mouth thoroughly with water.

Do NOT induce vomiting.

Call a physician immediately.

Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.



according to 29 CFR 1910.1200(g)

Cutting Fluid Silberschnitt V52

Revision date: 03/17/2022 Product code: BO5002904 Page 3 of 8

@1501.B015620

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. Fire-fighting measures

Water spray jet

Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2) Extinguishing powder alcohol resistant foam

Unsuitable extinguishing media

high volume water jet

Specific hazards arising from the chemical

Heating or fire can release toxic gas. Carbon dioxide, Carbon monoxide

Special protective equipment and precautions for fire-fighters

Standard procedure for chemical fires.

Self-contained respirator (breathing apparatus) according to OSHA Standard - 29 CFR: 1910.134 or ANSI 788.2.

Additional information

Use water spray to cool unopened containers.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

General advice

Use personal protective equipment.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Methods and material for containment and cleaning up

Other information

Provide adequate ventilation.

Prevent spread over a wide area (e.g. by containment or oil barriers).

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal. Dispose of waste according to applicable legislation.

Reference to other sections

Personal protection equipment (PPE): see section 8

Disposal: see section 13

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Provide adequate ventilation as well as local exhaustion at critical locations.

To avoid risks to man and the environment, comply with the instructions for use.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Usual measures for fire prevention.



according to 29 CFR 1910.1200(g)

Cutting Fluid Silberschnitt V52

Revision date: 03/17/2022 Product code: BO5002904 Page 4 of 8

Take precautionary measures against static discharges.

Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Do not breathe vapours or spray mist.

Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately.

Wash hands before breaks and immediately after handling the product.

When using do not eat or drink. Do not smoke.

Keep away from food, drink and animal feedingstuffs.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store in a place accessible by authorized persons only.

Protect from direct sunlight.

Hints on joint storage

Incompatible with oxidizing agents.

Further information on storage conditions

Recommended storage temperature: 5 - 40°C

8. Exposure controls/personal protection

Control parameters

Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaustion at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber), NBR (Nitrile rubber)

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

EN 13034 (type 6 limited splash-tight)

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Combination filtering device Respirator with filter for organic vapour, Recommended Filter type: A-P2

Environmental exposure controls

Do not flush into surface water or sanitary sewer system.

Do not allow to enter into soil/subsoil.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state: Liquid Color: colourless

Odor: like: Hydrocarbons



according to 29 CFR 1910.1200(g)

Cutting Fluid Silberschnitt V52

Revision date: 03/17/2022 Product code: BO5002904 Page 5 of 8

Test method

Changes in the physical state

Boiling point or initial boiling point and > 165 °C

boiling range:

Flash point: 59 °C ISO 2719

Lower explosion limits: not determined
Upper explosion limits: not determined
Auto-ignition temperature: not determined

Self-ignition temperature not auto-flammable

pH-Value: not applicable

Viscosity / dynamic: < 2 mPa·s

(at 20 °C)

Viscosity / kinematic: < 2 mm²/s

(at 40 °C)

Water solubility: insoluble Vapor pressure: 1 hPa

(at 20 °C)

Density (at 20 °C): 0,78 g/cm³

Other information

Other safety characteristics

Solvent content: 100%

Further Information

Vapors may form explosive mixtures with air.

10. Stability and reactivity

Reactivity

No hazardous reaction when handled and stored according to provisions.

Chemical stability

Stability: Stable

The mixture is chemically stable under recommended conditions of storage, use and temperature.

Possibility of hazardous reactions

Hazardous reactions: Will not occur

Vapors may form explosive mixtures with air.

Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Protect from direct sunlight.

Incompatible materials

oxidizing agents

Hazardous decomposition products

No decomposition if used as directed.

11. Toxicological information

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.



according to 29 CFR 1910.1200(g)

Cutting Fluid Silberschnitt V52

Revision date: 03/17/2022 Product code: BO5002904 Page 6 of 8

CAS No	Components							
	Exposure route	Dose		Species	Source	Method		
68551-17-7	Hydrocarbons, C10-C13, isoalkanes, cyclics, <2% aromatics							
	dermal	LD50 >3 mg/kg	3160	Rabbit				
93924-07-3	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics							
	oral	LD50 >5 mg/kg	5000	Rat				
	dermal	LD50 >5 mg/kg	5000	Rabbit				
	inhalation (4 h) vapour	LC50 >4 mg/l	4,951	Rat				
93924-07-3	Hydrocarbons, C11-C14, n-alkane, isoalkanes, cyclics, <2% aromatics							
	oral	LD50 >5 mg/kg	5000	Rat	OECD 401			
	dermal	LD50 >5 mg/kg	5000	Rabbit	OECD 402			

Irritation and corrosivity

Causes skin irritation

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitizing effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity (STOT) - repeated exposure

Based on available data, the classification criteria are not met.

Carcinogenicity (OSHA): No ingredient of this mixture is listed.
Carcinogenicity (IARC): No ingredient of this mixture is listed.
Carcinogenicity (NTP): No ingredient of this mixture is listed.

Aspiration hazard

May be fatal if swallowed and enters airways

12. Ecological information

Ecotoxicity

This product has no known eco-toxicological effects.

Bioaccumulative potential

Bioaccumulation is unlikely.

Mobility in soil

No data available

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Other adverse effects

slightly water endangering

Do not flush into surface water or sanitary sewer system.

Avoid subsoil penetration.



according to 29 CFR 1910.1200(g)

Cutting Fluid Silberschnitt V52

Revision date: 03/17/2022 Product code: BO5002904 Page 7 of 8

13. Disposal considerations

Waste treatment methods

Disposal recommendations

Can be incinerated, when in compliance with local regulations.

Contaminated packaging

Dispose of completely emptied containers as combustible waste or metal waste depending on the material.

14. Transport information

U.S. DOT 49 CFR 172.101

UN number or ID number: UN 3295

<u>Proper shipping name:</u> HYDROCARBONS, LIQUID, N.O.S.

Transport hazard class(es):

Packing group:
Hazard label:

3

3



Marine transport (IMDG)

UN number or ID number: UN 3295

UN proper shipping name: HYDROCARBONS, LIQUID, N.O.S.

Transport hazard class(es):

Packing group:

Hazard label:

3



Special Provisions: 223
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 3295

<u>UN proper shipping name:</u> HYDROCARBONS, LIQUID, N.O.S.

Transport hazard class(es):

Packing group:
Hazard label:

3

3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L

Environmental hazards



according to 29 CFR 1910.1200(g)

Cutting Fluid Silberschnitt V52

Revision date: 03/17/2022 Product code: BO5002904 Page 8 of 8

ENVIRONMENTALLY HAZARDOUS: No

15. Regulatory information

U.S. Regulations

National regulatory information

SARA Section 311/312 Hazards:

Hydrocarbons, C10-C13, isoalkanes, cyclics, <2% aromatics (68551-17-7): Fire hazard, Immediate (acute) health hazard

3-butoxypropan-2-ol, propylene glycol monobutyl ether (5131-66-8): Immediate (acute) health hazard

State Regulations

Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65, State of California)

This product can not expose you to chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

16. Other information

Hazardous Materials Information Label (HMIS)

Health: 1
Flammability: 2
Physical Hazard: 0

NFPA Hazard Ratings

Health: 1
Flammability: 2
Reactivity: 0

Unique Hazard:

Revision date: 17.03.2022 Revision No: 1,06



Other data

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)