

Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 1 of 9

1. Identification

Product identifier

Verifix 2K Silikon Primer Catalyst

Further trade names

- part of Set
- BO 5500510, 1 kg
- BO 5500513, 5 kg
- BO 5500516, 50 kg
- BO 5500518, 100 ml Primer

Recommended use of the chemical and restrictions on use

Use of the substance/mixture

catalyst

Details of the supplier of the safety data sheet

Manufacturer

Company name:	BOHLE AG	
Street:	Dieselstr. 10	
Place:	42781 Haan	
Telephone:	+49 2129 5568-0	Telefax: +49 2129 5568-282
e-mail:	info@bohle.de	
Contact person:	Dr. Martin Schade	Telephone: +49 2129 5568-300
e-mail:	MSDS@bohle.de	
Internet:	www.bohle.com	
Responsible Department:	Chemie	

Trader of the product

Company name:	Bohle America, Inc.
Street:	10924 Granite Street, Suite 200
Place:	USA-NC 28273 Charlotte
e-mail (Contact person):	sales@bohle.com

Emergency phone number: Emergency CONTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463

2. Hazard(s) identification

Classification of the chemical

Regulation (EC) No 1272/2008

- Flam. Liq. 2; H225
- Eye Irrit. 2; H319
- STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:



Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 2 of 9

Hazard statements

H225 Highly flammable liquid and vapor
 H319 Causes serious eye irritation
 H336 May cause drowsiness or dizziness

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P235 Keep cool.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 If eye irritation persists: Get medical advice/attention.

Additional advice on labelling

The product is classified and labelled in accordance with EC directives or respective national laws.

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Pictograms:

**3. Composition/information on ingredients****Mixtures****Chemical characterization**

ISOPROPYL ALCOHOL

Hazardous components

CAS No	Components			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			95 - < 100 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Components	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	99.1 %
	inhalation: LC50 = 30 mg/l (vapours); dermal: LD50 = 13400 mg/kg; oral: LD50 = 4570 mg/kg		

4. First-aid measures**Description of first aid measures****General information**

Take off immediately all contaminated clothing.

After inhalation

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

After contact with skin

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 3 of 9

After contact with eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists, consult a specialist.

After ingestion

Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Give sodium sulfate as laxative (1 tablespoon in 1 glass of water) with plenty of activated coal.

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

No information available.

5. Fire-fighting measures**Extinguishing media****Suitable extinguishing media**

water spray, alcohol-resistant foam, dry chemical, carbon dioxide (CO₂)

Unsuitable extinguishing media

high volume water jet

Specific hazards arising from the chemical

In use, may form flammable/explosive vapor-air mixture.
Fire may cause evolution of: Carbon monoxide, Carbon dioxide)

Special protective equipment and precautions for fire-fighters

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

Additional information

Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****General advice**

Use personal protective equipment. Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.
Keep away from heat and sources of ignition.
Avoid contact with skin and eyes. Do not breathe vapour.

Environmental precautions

Do not flush into surface water or sanitary sewer system.
Due to danger of explosion, prevent leakage of vapors into cellars, flues and ditches.
Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up**Other information**

Provide adequate ventilation. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Collect in closed and suitable containers for disposal.

Reference to other sections

Safe handling: see section 7
Personal protection equipment (PPE): see section 8
Disposal: see section 13

7. Handling and storage**Precautions for safe handling**

Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 4 of 9

Advice on safe handling

Provide adequate ventilation as well as local exhaust at critical locations.
 Provide room air exhaust at ground level.
 Avoid formation of aerosol. Do not breathe vapour/aerosol.
 Avoid contact with the skin and the eyes.

Advice on protection against fire and explosion

Take precautionary measures against static discharges. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke.

Advice on general occupational hygiene

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday.

Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

8. Exposure controls/personal protection
Control parameters
Exposure limits

CAS No.	Substance	ppm	mg/m ³	f/cc	Category	Origin
67-63-0	Isopropyl alcohol	400	980		TWA (8 h)	PEL
		400	980		TWA (8 h)	REL
		500	1225		STEL (15 min)	REL

DNEL/DMEL values

CAS No.	Substance	Exposure route	Effect	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			
Consumer DNEL, long-term		oral	systemic	26 mg/kg bw/day
Consumer DNEL, long-term		dermal	systemic	319 mg/kg bw/day
Worker DNEL, long-term		dermal	systemic	888 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	89 mg/m ³
Worker DNEL, long-term		inhalation	systemic	500 mg/m ³

PNEC values

CAS No.	Substance	Value
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	
Freshwater		140,9 mg/l
Freshwater (intermittent releases)		140,9 mg/l
Marine water		140,9 mg/l
Freshwater sediment		552 mg/kg
Marine sediment		552 mg/kg
Micro-organisms in sewage treatment plants (STP)		2251 mg/l
Soil		28 mg/kg

Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 5 of 9

Exposure controls

Appropriate engineering controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

Individual protection measures, such as personal protective equipment

Eye/face protection

safety glasses with side-shields conforming to EN166

Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Glove material: Butyl caoutchouc (butyl rubber) $\geq 0,5\text{mm}$, NBR (Nitrile rubber) $\geq 0,35\text{mm}$

Breakthrough time: ≥ 480 min.

Skin protection

impervious clothing

Respiratory protection

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state:	liquid
Color:	clear
Odor:	alcoholic

Test method

Changes in the physical state

Melting point/freezing point:	-89,5 °C
Boiling point or initial boiling point and boiling range:	82 °C
Flash point:	12 °C

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits:	2 vol. %
Upper explosion limits:	12 vol. %
Auto-ignition temperature:	425 °C

Self-ignition temperature

not auto-flammable

pH-Value (at 20 °C):	not applicable
Viscosity / dynamic: (at 20 °C)	2,4 mPa·s
Water solubility: (at 20 °C)	soluble
Vapor pressure: (at 20 °C)	48 hPa
Density (at 20 °C):	0,79 g/cm ³

Other information

Other safety characteristics

Solvent content:	99%
------------------	-----

Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 6 of 9

Further Information

10. Stability and reactivity

Reactivity

None under normal processing.

Chemical stability

No decomposition if used as directed.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Conditions to avoid

Keep away from heat and sources of ignition.
Take precautionary measures against static discharge.

Incompatible materials

strong acids and oxidizing agents

Hazardous decomposition products

None known.

11. Toxicological information

Information on toxicological effects

Acute toxicity

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol				
	oral	LD50 mg/kg	4570	Rat	
	dermal	LD50 mg/kg	13400	Rabbit	
	inhalation (4 h) vapour	LC50	30 mg/l	Rat	

Information on other hazards

Other information

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

12. Ecological information

CAS No	Components					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol					
	Acute fish toxicity	LC50 mg/l	9640	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	>2000	72 h	Desmodesmus subspicatus	

Persistence and degradability

Readily biodegradable, according to appropriate OECD test.

Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 7 of 9

Partition coefficient n-octanol/water

CAS No	Components	Log Pow
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol	-0,16

Mobility in soil

The product evaporates readily.

Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Water hazard class 1: slightly water endangering

Do not let product enter drains.

13. Disposal considerations**Waste treatment methods****Disposal recommendations**

In accordance with local and national regulations.

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150107 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); glass packaging

Contaminated packaging

Non-contaminated packages may be recycled.

Contaminated packages must be completely emptied and can be re-used following proper cleaning.

cleaning agent : Water

14. Transport information**Land transport (ADR/RID)****UN number or ID number:**

UN 1219

UN proper shipping name:

ISOPROPANOL (ISOPROPYL ALCOHOL)

Transport hazard class(es):

3

Packing group:

II

Hazard label:

3



Classification Code:

F1

Special Provisions:

601

Limited quantity:

1 L

Excepted quantity:

E2

Transport category:

2

Hazard No:

33

Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 8 of 9

Tunnel restriction code: D/E

Inland waterways transport (ADN)

UN number or ID number: UN 1219
UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Classification Code: F1
 Special Provisions: 601
 Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

UN number or ID number: UN 1219
UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Special Provisions: -
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1219
UN proper shipping name: Isopropanol
Transport hazard class(es): 3
Packing group: II
 Hazard label: 3



Special Provisions: A180
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

Special precautions for user

none

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not relevant

Verifix 2K Silikon Primer Catalyst

Revision date: 08/30/2022

Product code: BO5500510PC

Page 9 of 9

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 99 %

National regulatory information

Employment restrictions: Observe employment restrictions for young people.

Water hazard class (D): 1 - slightly hazardous to water

Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

16. Other information

Classification for mixtures and used evaluation method according to GHS

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H statements (full text)

- H225 Highly flammable liquid and vapor
- H319 Causes serious eye irritation
- H336 May cause drowsiness or dizziness

Other data

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)