

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 05/04/2022

Product code: BOMV76V10

Page 1 of 11

**1. Identification****Product identifier**

UV Adhesive VERIFIX MV 760 VIS

**Further trade names**

BO MV76V10, 100 g

BO MV76V25, 250 g / BO MV76V25S, Spacer, 250 g

BO MV76V1K, 1000 g

**Recommended use of the chemical and restrictions on use****Use of the substance/mixture**

adhesives

**Details of the supplier of the safety data sheet****Manufacturer**

Company name: BOHLE AG

Street: Dieselstr. 10

Place: 42781 Haan

Telephone: +49 2129 5568-0

Telefax: +49 2129 5568-282

e-mail: info@bohle.de

Contact person: Dr. Martin Schade

Telephone: +49 2129 5568-300

e-mail: MSDS@bohle.de

Internet: www.bohle.com

Responsible Department: Chemie

**Trader of the product**

Company name: Bohle America, Inc.

Street: 10924 Granite Street, Suite 200

Place: USA-NC 28273 Charlotte

e-mail (Contact person): sales@bohle.com

**Emergency phone number:** Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463**2. Hazard(s) identification****Classification of the chemical****Regulation (EC) No 1272/2008**

Skin Corr. 1A; H314

Eye Dam. 1; H318

Skin Sens. 1; H317

STOT SE 3; H335

Aquatic Acute 1; H400

Aquatic Chronic 1; H410

Full text of hazard statements: see SECTION 16.

**Label elements****Regulation (EC) No 1272/2008****Hazard components for labelling**

Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate

acrylic acid, prop-2-enoic acid

2-hydroxyethyl methacrylate

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

**Signal word:** Danger

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 05/04/2022

Product code: BOMV76V10

Page 2 of 11

**Pictograms:**

**Hazard statements**

H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H335	May cause respiratory irritation
H411	Toxic to aquatic life with long lasting effects

**Precautionary statements**

P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P301+P330+P331	If swallowed: Rinse mouth. Do NOT induce vomiting.
P310	Immediately call a poison center/doctor.

**3. Composition/information on ingredients**
**Mixtures**
**Chemical characterization**

Methacrylate/Acrylate resin(s).

**Hazardous components**

CAS No	Components			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate			40 - < 45 %
	227-561-6		01-2119957862-25	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H315 H319 H317 H335 H400 H410			
73324-00-2	Urethane acrylate			30 - < 35 %
	615-966-4		-	
	Skin Irrit. 2, Eye Irrit. 2; H315 H319			
79-10-7	acrylic acid, prop-2-enoic acid			15 - < 20 %
	201-177-9	607-061-00-8	01-2119452449-31	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Corr. 1A, Aquatic Acute 1; H226 H332 H312 H302 H314 H400			
868-77-9	2-hydroxyethyl methacrylate			5 - < 10 %
	212-782-2	607-124-00-X	01-2119490169-29	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1; H315 H319 H317			
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			1 - < 5 %
	278-355-8	015-203-00-X	01-2119972295-29	
	Repr. 2, Skin Sens. 1B, Aquatic Acute 2, Aquatic Chronic 2; H361f H317 H401 H411			

Full text of H and EUH statements: see section 16.

## UV Adhesive VERIFIX MV 760 VIS

Revision date: 05/04/2022

Product code: BOMV76V10

Page 3 of 11

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Components	Quantity
		Specific Conc. Limits, M-factors and ATE	
5888-33-5	227-561-6	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	43.52 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg M acute; H400: M=1 M chron.; H410: M=1	
79-10-7	201-177-9	acrylic acid, prop-2-enoic acid	17.5 %
		inhalation: LC50 = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 1100 mg/kg; oral: LD50 = 500 mg/kg STOT SE 3; H335: >= 1 - 100 M acute; H400: M=1	
868-77-9	212-782-2	2-hydroxyethyl methacrylate	7.5 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = 5050 mg/kg	
75980-60-8	278-355-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	1.48 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	

## 4. First-aid measures

### Description of first aid measures

#### General information

First aider: Pay attention to self-protection!  
Get medical advice/attention if you feel unwell.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. If symptoms persist, call a physician.

#### After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. When in doubt or if symptoms are observed, get medical advice.

#### After contact with eyes

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.

#### After ingestion

Do not induce vomiting. Immediately give large quantities of water to drink. Call a physician immediately.

### Most important symptoms and effects, both acute and delayed

Inhalation: Irritation to respiratory tract  
Skin contact : May cause an allergic skin reaction.  
Eye contact : Causes serious eye damage.

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## 5. Fire-fighting measures

### Extinguishing media

#### Suitable extinguishing media

Water spray jet, Extinguishing powder, Foam, Carbon dioxide (CO2)

#### Unsuitable extinguishing media

Full water jet

### Specific hazards arising from the chemical

Burning produces irritant fumes. Carbon monoxide, Carbon dioxide, Hydrocarbons, Nitrogen oxides (NOx)

### Special protective equipment and precautions for fire-fighters

Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
In the event of fire, wear self-contained breathing apparatus.

## UV Adhesive VERIFIX MV 760 VIS

Revision date: 05/04/2022

Product code: BOMV76V10

Page 4 of 11

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

##### General advice

Wear personal protection equipment (refer to section 8).  
Provide adequate ventilation.

#### Environmental precautions

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration.  
Local authorities should be advised if significant spillages cannot be contained.

#### Methods and material for containment and cleaning up

##### Other information

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. Ensure adequate ventilation.

#### Reference to other sections

Personal protection equipment (PPE): see section 8  
Disposal: see section 13

### 7. Handling and storage

#### Precautions for safe handling

##### Advice on safe handling

Avoid contact with skin and eyes.  
Do not eat, drink or smoke when using this product.  
Ensure adequate ventilation.

##### Advice on protection against fire and explosion

No special technical protective measures required.

##### Advice on general occupational hygiene

Wash hands before breaks and after work. When using do not eat, drink or smoke.  
Take off immediately all contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

##### Further information on handling

Avoid: UV-radiation/sunlight

#### Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place.  
Keep container tightly closed. Keep locked up.  
Recommended storage temperature 5 - 25°C. Keep away from direct sunlight.

#### Specific end use(s)

adhesive

### 8. Exposure controls/personal protection

#### Control parameters

##### Exposure limits

CAS No.	Substance	ppm	mg/m <sup>3</sup>	f/cc	Category	Origin
79-10-7	Acrylic acid	2	6		TWA (8 h)	REL

## UV Adhesive VERIFIX MV 760 VIS

Revision date: 05/04/2022

Product code: BOMV76V10

Page 5 of 11

### DNEL/DMEL values

CAS No.	Substance			
DNEL type	Exposure route		Effect	Value
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate			
Worker DNEL, long-term		dermal	systemic	1,39 mg/kg bw/day
79-10-7	acrylic acid, prop-2-enoic acid			
Worker DNEL, long-term		inhalation	systemic	30 mg/m³
Worker DNEL, acute		inhalation	systemic	30 mg/m³
Worker DNEL, long-term		inhalation	local	30 mg/m³
Worker DNEL, acute		inhalation	local	30 mg/m³

### PNEC values

CAS No.	Substance		
Environmental compartment	Value		
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate		
Freshwater	0,00092 mg/l		
Marine water	0,000092 mg/l		
Freshwater sediment	0,145 mg/kg		
Marine sediment	0,0145 mg/kg		
Micro-organisms in sewage treatment plants (STP)	2 mg/l		
Soil	0,0285 mg/kg		
79-10-7	acrylic acid, prop-2-enoic acid		
Freshwater	0,003 mg/l		
Freshwater (intermittent releases)	0,0013 mg/l		
Marine water	0,0003 mg/l		
Freshwater sediment	0,0236 mg/kg		
Marine sediment	0,00234 mg/kg		

### Exposure controls

#### Individual protection measures, such as personal protective equipment

##### Eye/face protection

safety glasses with side-shields conforming to EN166

##### Hand protection

The selected protective gloves have to satisfy the specifications of EU Directive 89/689/EEC and the standard EN 374 derived from it.

Recommended material: NBR (Nitrile rubber), VITON

Unsuitable material: Natural fibres (e.g. cotton)

##### Skin protection

Wear suitable protective clothing.

##### Respiratory protection

Usually no personal respiratory protection necessary. When using do not eat, drink or smoke.

In case of inadequate ventilation wear respiratory protection. Full-/half-/quarter-face masks (EN 136/140)

Respirator with filter for organic vapour. Recommended Filter type: A (P2)

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 05/04/2022

Product code: BOMV76V10

Page 6 of 11

**9. Physical and chemical properties****Information on basic physical and chemical properties**

Physical state:	Liquid
Color:	colorless
Odor:	characteristic

**Changes in the physical state**

Viscosity / dynamic: (at 23 °C)	1500 mPa·s
------------------------------------	------------

**Other information****Other safety characteristics**

Solvent content:	0%
------------------	----

**Further Information**

not auto-flammable

**10. Stability and reactivity****Reactivity**

Light / UV-radiation/sunlight  
Oxidizing agent, strong

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of hazardous reactions**

No known hazardous reactions.

**Conditions to avoid**

Keep cool. Protect from sunlight. Heat, flames and sparks.  
In case of light influence: Polymerisation

**Incompatible materials**

Reducing agent, strong. Oxidizing agent, strong  
strong acids and strong bases

**Hazardous decomposition products**

No decomposition if stored and applied as directed.  
Thermal decomposition can lead to the escape of irritating gases and vapors. Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Hydrocarbons

**11. Toxicological information****Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

**UV Adhesive VERIFIX MV 760 VIS**

Revision date: 05/04/2022

Product code: BOMV76V10

Page 7 of 11

CAS No	Components				
	Exposure route	Dose	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
79-10-7	acrylic acid, prop-2-enoic acid				
	oral	LD50 500 mg/kg	Rat		
	dermal	LD50 1100 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 11 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
868-77-9	2-hydroxyethyl methacrylate				
	oral	LD50 5050 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
	dermal	LD50 >2000 mg/kg	Rat	OECD 402	

**Irritation and corrosivity**

Causes severe skin burns and eye damage

Causes serious eye damage

**Sensitizing effects**

May cause an allergic skin reaction (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate; 2-hydroxyethyl methacrylate; Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide)

**Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

**Specific target organ toxicity (STOT) - single exposure**

May cause respiratory irritation (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate; acrylic acid, prop-2-enoic acid)

Inhalative specific target organ toxicity (single exposure)

@05888.33.5DE: Category 3

acrylic acid; prop-2-enoic acid: Category 3

**Specific target organ toxicity (STOT) - repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**12. Ecological information**

## UV Adhesive VERIFIX MV 760 VIS

Revision date: 05/04/2022

Product code: BOMV76V10

Page 8 of 11

CAS No	Components					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate					
	Acute fish toxicity	LC50 mg/l	0,704	96 h	Danio rerio (zebrafish)	OECD 203
	Crustacea toxicity	NOEC mg/l	0,092	21 d	Daphnia magna (Big water flea)	
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas	
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide					
	Acute fish toxicity	LC50	10 mg/l	96 h	Danio rerio (zebrafish)	
	Acute crustacea toxicity	EC50 mg/l	3,53	48 h	Daphnia magna (Big water flea)	OECD 202
	Acute bacteria toxicity	(EC50 mg/l)	2,01		Pseudokirchneriella subcapitata	OECD 201

CAS No	Components			
	Method	Value	d	Source
	Evaluation			
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate			
		57%	28	
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide			
	aerob	0-10%	28	
	Not readily biodegradable (according to OECD criteria)			

## Partition coefficient n-octanol/water

CAS No	Components	Log Pow
5888-33-5	Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate	4,52
79-10-7	acrylic acid, prop-2-enoic acid	0,35
868-77-9	2-hydroxyethyl methacrylate	0,47

## BCF

CAS No	Components	BCF	Species	Source
75980-60-8	Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	18-22		

## Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

## Further information

No data is available on the product itself.

## 13. Disposal considerations

## Waste treatment methods

## Disposal recommendations

Consult the appropriate local waste disposal expert about waste disposal.

## List of Wastes Code - used product

## UV Adhesive VERIFIX MV 760 VIS

Revision date: 05/04/2022

Product code: BOMV76V10

Page 9 of 11

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

### Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

## 14. Transport information

### Land transport (ADR/RID)

**UN number or ID number:** UN 1760  
**UN proper shipping name:** CORROSIVE LIQUID, N.O.S. (acrylic acid; prop-2-enoic acid)  
**Transport hazard class(es):** 8  
**Packing group:** III  
Hazard label: 8



Classification Code: C9  
Special Provisions: 274  
Limited quantity: 5 L  
Excepted quantity: E1  
Transport category: 3  
Hazard No: 80  
Tunnel restriction code: E

### Inland waterways transport (ADN)

**UN number or ID number:** UN 1760  
**UN proper shipping name:** CORROSIVE LIQUID, N.O.S. (acrylic acid; prop-2-enoic acid)  
**Transport hazard class(es):** 8  
**Packing group:** III  
Hazard label: 8



Classification Code: C9  
Special Provisions: 274  
Limited quantity: 5 L  
Excepted quantity: E1

### Marine transport (IMDG)

**UN number or ID number:** UN 1760  
**UN proper shipping name:** CORROSIVE LIQUID, N.O.S.. (Acrylic Acid)  
Marine pollutant (@05888.33.5DE, Acrylic Acid)  
**Transport hazard class(es):** 8  
**Packing group:** III  
Hazard label: 8

## UV Adhesive VERIFIX MV 760 VIS

Revision date: 05/04/2022

Product code: BOMV76V10

Page 10 of 11



Special Provisions: 223, 274  
 Limited quantity: 5 L  
 Excepted quantity: E1  
 EmS: F-A, S-B

### Air transport (ICAO-TI/IATA-DGR)

UN number or ID number: UN 1760  
UN proper shipping name: CORROSIVE LIQUID, N.O.S. (Acrylic Acid)  
Transport hazard class(es): 8  
Packing group: III  
 Hazard label: 8



Special Provisions: A3 A803  
 Limited quantity Passenger: 1 L  
 Passenger LQ: Y841  
 Excepted quantity: E1  
 IATA-packing instructions - Passenger: 852  
 IATA-max. quantity - Passenger: 5 L  
 IATA-packing instructions - Cargo: 856  
 IATA-max. quantity - Cargo: 60 L

### Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



## 15. Regulatory information

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): 0 %  
 0 g/l

Information according to 2012/18/EU (SEVESO III): E1 Hazardous to the Aquatic Environment

#### National regulatory information

Employment restrictions: Observe employment restrictions for young people.  
 Water hazard class (D): 3 - highly hazardous to water

### Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## 16. Other information

### Changes

This data sheet contains changes from the previous version in section(s): 2,3.

## UV Adhesive VERIFIX MV 760 VIS

Revision date: 05/04/2022

Product code: BOMV76V10

Page 11 of 11

### Classification for mixtures and used evaluation method according to GHS

Classification	Classification procedure
Skin Corr. 1A; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method
STOT SE 3; H335	Calculation method
Aquatic Acute 1; H400	Calculation method
Aquatic Chronic 1; H410	Calculation method

### Relevant H statements (full text)

H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H361f	Suspected of damaging fertility
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

### Other data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*